

Dependable Heat Wherever You Need It

Keep your work site warm this winter with an indirect fired heater by Flagro.

- Flagro 200: 200,000 BTU/hr - Up To 1500 CFM
- Flagro 400: 390,000 BTU/hr - Up To 2500 CFM
- Diesel, kerosene, propane, natural gas options



**STAY
WARM
THE
WINTER**

BUILT ARCTIC TOUGH

www.EquipmentSourceInc.com



FVO-200

Diesel & Kerosene
Built-in fuel tank

FVN-200 / FVP-200

Natural Gas / Propane

FVO-400

Diesel & Kerosene
Built-in fuel tank

FVNP-400

Natural Gas & Propane

Be prepared for winter. Buy a Flagro today!

Choose between two output levels - 200,000 or 390,000 BTU/hr - and all major fuel types. Standard features include:

- **Stainless steel heat exchangers**
- **Proven Riello burner technology**
- **Slim designs with wheels for easy mobility & transport**
- **Input jacks for optional remote thermostat**
- **ETL approval for use in the US & Canada**

The Flagro 200 & 400 indirect fired heaters are perfect for any heating application where clean hot air is needed.

- Heating construction work sites, both indoors and out.
- Heating and de-humidifying industrial/commercial facilities.
- Keeping maintenance shacks warm.
- Help control moisture for sub-ground construction.
- Duct in safe heat to mine shafts.
- Also great for emergency heat, thawing applications, equipment start-up, and outdoor event heating.

	FVO-200	FVN-200	FVP-200	FVO-400	FVNP-400
Fuel type	No.1, No. 2, diesel or kerosene	Natural Gas	Propane	No.1, No. 2, diesel or kerosene	Dual Fuel
Heat		200,000 BTU/h		390,000 BTU/h	
Airflow		1600 CFM		2500 CFM	
Fuel consumption	1.50 gph	190 cfh	9.25 lb/h	2.75 gph	Nat. Gas: 390 cfh Propane: 18.5 lb/h
Fuel tank	23 gal capacity 15 hour run time	External		42 gal capacity 14 hour run time	External
Heat exchanger		18 gauge 304 Stainless Steel		16 gauge 304 Stainless Steel	
Ignition		Direct Spark Ignition			
Power requirements		115V / 60Hz / 15A			
Approvals		cETLus		cWHus, ETL	
Dimensions	51.5" x 27" x 43.5"	53.5" x 27" x 39.5"		70" x 29" x 52"	70" x 29" x 47"
Weight	330 lb	280 lb		450 lb	365 lb
Wheels	Two 12" pneumatic / Two 6" lockable swivel casters			Two 16" pneumatic	

