

Quiet, versatile, and powerful.

- Fuel-efficient Isuzu engine
- Provides both single and three-phase output
- Ultra Quiet Technology
- ESI-exclusive Re-Air option regulates airflow to maintain constant temperature within the enclosure



GENERATORS

BUILT ARCTIC TOUGH

www.EquipmentSourceInc.com

Features & benefits

- Rugged, fuel-efficient Isuzu diesel engine
- 58.6 gallon fuel capacity
- Ultra Quiet Technology for class-leading sound level reduction
- Lightweight and compact to fit into tight spaces
- Connects easily and is simple to operate
- Two-way tank valve for easy connection with auxiliary tanks
- Voltage selector permits matching output to load
- Lockable switch protects against improper voltage change
- Provides both single and three-phase output
- Low oil pressure and high coolant temperature result in automatic shut-down
- Durable all-weather outer enclosure with powder coated exterior and stainless steel fasteners

Available mounting

- Skid mounted (standard)
- Trailer mounted

Options

- ESI-exclusive Re-Air attachment regulates airflow to maintain a constant temperature within the enclosure



Specifications

Generator type	Revolving field brushless AC 3 Phase-120/240V Single Phase
Frequency	60 Hz
Output	Three-phase: 100 kVA / 80 kW Single-phase: 58 kW
Voltage	Three-phase: 208, 240, 480 V Single-phase: 120, 139, 240, 277 V
Current	Three-phase 240V: 241A Three-phase 480V: 120A Single-phase 120V: 242 A x 2 (ZigZag) Single-phase 240V: 242 A (ZigZag)