

# Maximum power. Minimal noise.

- Provides both single and three-phase output
- Single-phase 240V output available in all voltage settings
- Ultra Quiet Technology
- ESI-exclusive Re-Air option regulates airflow to maintain constant temperature within the enclosure



**GENERATORS**

**BUILT ARCTIC TOUGH**  
[www.EquipmentSourceInc.com](http://www.EquipmentSourceInc.com)

**Features & benefits**

- Rugged, fuel-efficient Isuzu diesel engine
- 74 gallon fuel capacity
- Ultra Quiet Technology for class-leading sound level reduction
- Lightweight and compact to fit into tight spaces
- Provides both single and three-phase output
- Single-phase 240V output available in all voltage settings
- Low oil pressure and high coolant temperature result in automatic shut-down
- Thermal relay opens main circuit breaker to protect generator in case of overload
- Durable all-weather outer enclosure with powder coated exterior and stainless steel fasteners
- Two-way tank valve for easy connection with auxiliary tanks

**Available mounting**

- Skid mounted (standard)
- Trailer mounted

**Options**

- ESI-exclusive Re-Air attachment regulates airflow to maintain a constant temperature within the enclosure


**Specifications**

Generator type	Rotating field, brushless 3-phase synchronous alternator
Frequency	60 Hz
Output	<b>Three-phase:</b> 150 kVA / 120 kW <b>Single-phase:</b> 90 kW
Voltage	<b>Three-phase:</b> 208, 480 V <b>Single-phase:</b> 120, 240, 277 V
Current	<b>Three-phase 208V:</b> 416A <b>Three-phase 480V:</b> 180A <b>Single-phase 120V:</b> 361 A x 2 (ZigZag) <b>Single-phase 240V:</b> 361 A (ZigZag)